

2 Installation

2.1 Check Device Check device shell and its accessories before installation

2.2 Install the device

A.Waterproof: Please choose somewhere is waterproof. Be careful to let device stay away from the air conditioning outlet to prevent condensate water from accumulating, which can avoid damaging the service life of the product.

B.Shakeproof: Do not install the devicein the position with large vibration amplitude.

C.Tamper-proof: GPS Device should be away from electronic equipment to prevent signal interference.



2.3 Installation Precautions

Device magnetic cannot touch somewhere high temperature, for example, car exhaust pipe, otherwise will make magnetic useless

Please do the payment for the SIM Card per month or per year continuously, device cannot be used if overdue.

Device should be tested after the first installation.

The strong magnetic on the back of device cannot touch the hard disk digital products, which will cause damage to the hard disk.

If any questions, please contact us for help.

3 LED Indicator

LED Indicator	LED Indicator Status	
Power LED Indicator (Red)	Long light:External power supply is charging	
	Slowly blinking:Power supply or battery full charged	
	Quickly blinking:Low backup battery	
	No light:LED Indicator broken or sleeping mode	
GSM LED Indicator (Yellow)	Quickly blinking:GSM initialization	
	Slowly blinking:GSM received normal signal	
	No light:Sleeping mode or no GSM internet	
Location LED indicator (Blue)	Quickly blinking:Searching signal	
	Slowly blinking:Signal normal	
	No light:GPS in sleep mode or abnormal working	

4 Device features list

Main features	Description		
SOS set or delete	3 SOS numbers can be set or delete		
Over-speed alarm	You will receive alarm if over-speed		
Voice monitoring	The SOS number dials the phone number on the device and immediately enters the monitoring state. (note: this function can only be supported by voice card)		
Geo-fence	You will receive alarm if GPS drive out in somewhere limited		
Shock alarm	You will receive shock alarm when car shocked after turn on its defensive state.		
Low battery alarm	You will receive low battery alarm once turn on low battery notification		
Intelligent power saving mode	Unit set is seconds, default is 10 seconds to locate, which is the most accurate mode, G-SENSOR control gps working at the end working 4 minutes each time.		
Time interval working mode	The unit of time is minutes, and a range of 5-1440 minutes can be set for reporting		
GPS/BDS	When no GPS or BDS signal is found, the base station is automatically started for positioning		
Cut-wire alarm	Light detection oil dark to light to achieve the alarm dismantling		
Free installation	Strong magnetic, free of installation		

5 Access to platform

 Platform(www.wanwaygps.com)
Android and IOS APP Trackway There are two methods to login in the platform or app. 1. Login by IMEI number(the 15 digits in the back of the device), password: the last 6 digits of imei number.

2. Contact the supplier to create an account for you.

6 Precautions

- > Device warranty not including the damage of human factor.
- > Do not put device or its built-in battery in water or fire,
- do not bend or open the battery.
- > Do not disassemble device, which may cause damage for device due to un-professional handing.

Solutions to common problems

Please contact to sales when you cannot handle problems.

Common problem	Fault description	Solutions	
Poor signal	Some poor signal areas like basement, tunnels are not able to acquire GPS signal.	Move device to open sky areas.	
1 OOI Signal	Device cannot acquire GPS signal if placed face down or above with metal material layer shielding	Please put in the correct direction or change the installation position	
Unable to boot	Backup battery used up	Full charged before using	
Cannot connect internet	SIM Card no data service	Please contact SIM Card operator check data service	

Warranty policy

Special statement This product is subject to any technical change without prior notice. Product appearance and color are subject to the real product.

Replacement policy

We can replace a new one for you if device not damaged by human factor.



Power on and Power off

Power on: Long press the switch for more than 3 seconds, the main LED indicator quick flashing, which means working normally, then LED indicator extinguished, which means device enter sleep working mode.

Charging

Open the device silicone plug, connect to external power, red LED indicator long light means device charging, power LED slow flashing means device full charged.

Warranty Card

Customers Data

Customers Name	Telephone	
Address		
Model Type	IMEI number	
Purchase Data	Invoice No	
Company Address		

Please reserve the warranty card carefully

FCC Statement:

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment .This equipment should be installed and operated with minimum distance 20cm between the radiator& your body.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.